

# 03 - Manipulating Files and Using Git

CS 2043: Unix Tools and Scripting, Spring 2016 [1]

---

Stephen McDowell

February 1st, 2016

Cornell University

# Table of contents

1. Working with Files
2. Types of Files and Usages
3. Let's Git Started
4. Demo Time!

## Some Logistics

- Last day to add is Wednesday 2/3.
- HW0: Due today at 5pm.
- My OH are Tuesdays 6:00pm - 7:00pm, Gates G19.
- On moving forward independently, and using **sudo**.
  - I strongly advise taking a *snapshot* of your VM.
- A note about HW1...

# Working with Files

---

# Users and Groups

Like most OS's, Unix allows multiple people to use the same machine at once. The question: who has access to what?

- Access to files depends on the users' account.
- All accounts are presided over by the Superuser, or **root** account.
- Each user has absolute control over any files they own, which can only be superseded by **root**.
- Files can also be owned by a **group**, allowing more users to have access.

# File Ownership

You can discern who owns a file many ways, the most immediate being `ls -l`

## Permissions with `ls`

```
>>> ls -l Makefile
-rw-rw-r--. 1 sven users 4.9K Jan 31 04:42 Makefile
          sven      # the user
                users # the group
```

The third column is the *user*, and the fourth column is the *group*.

# What is this RWX Nonsense?

- R = read, W = write, X = execute.
- `rwxrwxrwx`
  - User permissions.
  - Group permissions.
  - Other permissions (a.k.a. neither the owner, nor a member of the group).
- Directory permissions begin with a **d** instead of a `-`.

## An example

What would the permissions `-rwxr-----` mean?

- It is a file.
- User can read and write to the file, as well as execute it.
- Group members are allowed to read the file, but cannot write to or execute.
- Other cannot do *anything* with it.



# Changing Permissions

## Change Mode

```
chmod <mode> <file>
```

- Changes file / directory permissions to **<mode>**.
- The format of **<mode>** is a combination of three fields:
  - Who is affected: a combination of **u**, **g**, **o**, or **a** (all).
  - Use a **+** to add permissions, and a **-** to remove.
  - Specify type of permission: any combination of **r**, **w**, **x**.
- Or you can specify mode in octal: user, then group, then other.
  - e.g. **777** means user=7, group=7, other=7 permissions.

The octal version can be confusing, but will save you time.  
Excellent resource in [2].

# Changing Ownership

Changing the group

## Change Group

```
chgrp group <file>
```

- Changes the group ownership of <file> to **group**.

As the super user, you can change who owns a file:

## Change Ownership

```
chown user:group <file>
```

- Changes the ownership of <file>.
- The **group** is optional.
- The **-R** flag is useful for recursively modifying everything in a directory.

## File Ownership, Alternate

If you are like me, you often forget which column is which in `ls -l...`

### Status of a file or filesystem

`stat [opts] <filename>`

- Gives you a wealth of information, generally more than you will every actually need.
- **U**id is the user, **G**id is the group.
  - BSD/OSX: use `stat -x` for standard display of this command.
- Can be useful if you want to mimic file permissions you don't know.
  - Human readable: - `format=%A`, e.g. `-rw-rw-r--`
    - BSD/OSX: `-f %Sp` is used instead.
  - Octal: - `format=%a` (great for `chmod`), e.g. `664`
    - BSD/OSX: `-f %A` is used instead.

## Platform Notes

- Convenience flag for `chown` and `chmod` on non-BSD Unix:

```
>>> chmod --reference=<src> <dest>
```

- Set the permissions of `dest` to the permissions of `src`!
- BSD/OSX users: `--reference` does not exist, you will have to execute two commands.

```
>>> chmod `stat -f %A <src>` <dest>
```

- The `stat` command inside of the ``backticks`` gets evaluated *before* `chmod` does.
- The `stat` command performs a little differently on BSD/OSX by default. Read the `man` page.

# Types of Files and Usages

---

Plain text files are human-readable, and are usually used for things like:

- Documentation,
- Application settings,
- Source code,
- Logs, and
- Anything you may want to read via the terminal (e.g. README.txt).

Binary files are not human-readable. They are written in the language your computer prefers.

- Executables,
- Libraries,
- Media files,
- Archives (.zip, etc), and many more.

# Reading Files Without Opening

## Concatenate

```
cat <filename>
```

- Prints the contents of the file to the terminal window

```
cat <file1> <file2>
```

- Prints `file1` first, then `file2`.

## more

```
more <filename>
```

- Scroll through one page at a time.
- Program exits when end is reached.

## less

```
less <filename>
```

- Scroll pages or lines (mouse wheel, space bar, and arrows).
- Program does not exit when end is reached.



Long files can be a pain with the previous tools.

## Head and Tail of Input

```
head -[numlines] <filename>
```

```
tail -[numlines] <filename>
```

- Prints the first / last numlines of the file.
- Default is 10 lines.

You can talk to yourself in the terminal too!

## Echo

```
echo <text>
```

- Prints the input string to the standard output (the terminal).
- We will soon learn how to use **echo** to put things into files, append to files, etc.

# Let's Git Started

---

## Another Brief Git Demo

If you are not at lecture, don't worry about this slide not making any sense.

```
>>> git clone <url>      # get a local copy
>>> git status           # informs you of changes
>>> git add <file(s)>    # if you need it online
>>> git commit          # saves this version
>>> git push            # puts the commit online
```

Demo Time!

---

# Our first in class demo

Instructions are here:

<https://github.com/cs2043-sp16/lecture-demos/tree/master/lec03>

## References I

[1] B. Abrahao, H. Abu-Libdeh, N. Savva, D. Slater, and others over the years.

**Previous cornell cs 2043 course slides.**

[2] C. Hope.

**Linux and unix chmod command help and examples.**

<http://www.computerhope.com/unix/uchmod.htm>,  
2016.